

SET LAUFEN PRO N

Floorstanding WC combination with cistern with fixing holes for floor fixation

82795.2



TECHNICAL DATA

Order no.	82795.2
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 737 2 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	34,5 kg
Accessories excl.	Seat and cover, order no. 89095.2 Seat and cover with automatic lowering system, order no. 89095.3
Mounting acc. incl.	Fastening kit, order no. 89175.7

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC pan washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 890 mm
outlet horizontal, VARIO vertical 70 - 250 mm
back to wall, concealed fixation, 2 fixing holes
Special feature: concealed surfaces directing water are fully glazed throughout, open water rim, vacuum checked
Further options / accessories: Surface refinement LCC, WC seat and cover, 89095.2, WC seat and cover with automatic lowering 89095.3
Order no. 82795.2

TECHNICAL DRAWINGS / S 1 : 20

